

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
12 February 2004 (12.02.2004)

PCT

(10) International Publication Number
WO 2004/013778 A3

(51) International Patent Classification⁷: **G06F 17/50**

(21) International Application Number:
PCT/JP2003/009821

(22) International Filing Date: 1 August 2003 (01.08.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2002-225860 2 August 2002 (02.08.2002) JP

(71) Applicant (for all designated States except US): **YAZAKI CORPORATION [JP/JP]**; 4-28, Mita 1-chome, Minato-ku, Tokyo 108-8333 (JP).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **SUGIHARA, Kokichi [JP/JP]**; c/o THE UNIVERSITY OF TOKYO,

3-1, Hongo 7-chome, Bunkyo-ku, Tokyo 113-0033 (JP).
SAWAI, Masayoshi [JP/JP]; c/o Yazaki Parts Co., Ltd.,
2464-48, Washizu, Kosai-shi, Shizuoka 431-0431 (JP).

(74) Agents: **OGURI, Shohei et al.**; Eikoh Patent Office, 28th Floor, ARK Mori Building, 12-32, Akasaka 1-chome, Minato-ku, Tokyo 107-6028 (JP).

(81) Designated States (national): AU, CN, KR, US.

(84) Designated States (regional): European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR).


Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

(88) Date of publication of the international search report:
10 September 2004

[Continued on next page]

(54) Title: **METHOD OF CALCULATING A WIRE PACKING DIAMETER, APPARATUS THEREFOR, AND PROGRAM THEREFOR**



(57) **Abstract:** To provide an effective calculation method and an apparatus therefor for obtaining an outside diameter of a wire packing by bundling and packing a plurality of wires into the smallest possible circular shape. The outside diameter of a wire harness surrounding a plurality of wires is efficiently obtained by repeatedly calculating an operation in which the layout of the plurality of wires making up the wire harness is changed such that, by using a computer, the wires are moved as distantly as possible from the wire protruding from an including circle, and the protruding wire is inserted in a space thus created. In particular, by adopting the concept of a circular Voronoi diagram, it becomes possible to obtain the outside diameter of the wire harness extremely simply and in a short time.